

Tables and Queries With **aRT**

Pedro Ribeiro de Andrade Neto
Paulo Justiniano Ribeiro Júnior

December 7, 2007

Contents

1	Introduction	1
2	Static tables	2
2.1	External tables	5
2.2	Media tables	6
3	Attribute queries	7
3.1	Join tables	7
3.2	Attribute restrictions	7
3.3	Spatial queries	7
4	Temporal Tables	7
4.1	Event tables	8
4.2	Dynamic attribute tables	10
4.3	Dynamic geometry tables	10
4.4	Fully dynamic tables	10
5	Temporal queries	10
5.1	Joining tables	10
5.2	Temporal slicing	10

1 Introduction

In **aRT** there are seven types of table, implementing the TerraLib models. They are:

- static,
- external,
- media,
- event,

- dynatt,
- dynggeom, and
- alldyn.

These tables are encapsulated in the class **aRTtable**, and we can query them using **aRTtheme** and **aRTquerier** objects. The three classes are discussed in this document, and we present here how to execute database queries, selecting and joining attributes.

```
> library(aRT)
```

```
-----
R-TERRALIB API
```

```
aRT version 1.4-2 (2007-11-28) is now loaded
-----
```

```
> conn = openConn()
> if (any(showDbs(conn) == "tabletest")) deleteDb(conn, "tabletest",
+       force = T)
> db = createDb(conn, db = "tabletest")
```

We will create a new layer, populate with some geometries, and, for each type of table, we discuss how to populate the table, and how to make temporal and attributes queries, using the other **aRT** classes. Note that spatial querier can be done directly using **aRTlayer** objects.

```
> quantity = 10
> xc = round(runif(quantity), 2)
> yc = round(runif(quantity), 2)
> xy = cbind(xc, yc)
> xy.sp = SpatialPoints(xy)
> xy.spdf = SpatialPointsDataFrame(xy, data.frame(ID = paste(1:quantity)))

> lstatic = createLayer(db, l = "static")
> addPoints(lstatic, xy.spdf)
```

All non-geometric data in **aRT** is stored in tables, and the way to exchange this type of information with the database is using **aRTtable** objects. **aRTtable** objects are created and opened from **aRTlayer** objects, using **createTable** and **openTable**, respectively. Table data is read from and written to databases using **data.frame**. **row.names** are not used to represent IDs in **aRT**, because IDs can be unsufficient to describe temporal data.

2 Static tables

The most basic type of table in **aRT** is *static*. Static tables store attributes with no variation in the time, for example the object **df** below:

```
> id = getID(xy.spdf)
> norm = unlist(lapply(id, function(x) rnorm(1, 20, 10)))
> unif = unlist(lapply(id, function(x) runif(1, 1, 100)))
> df = data.frame(id, norm, unif)
> df
```

	id	norm	unif
1	1	11.984301	97.89574
2	2	19.713813	31.62978
3	3	15.566071	89.62430
4	4	21.704297	56.84160
5	5	6.500174	38.60381
6	6	6.332662	36.27251
7	7	11.063396	63.53696
8	8	32.873980	23.49168
9	9	34.684389	11.19028
10	10	7.358129	91.07037

To create a static table in a layer we use `createTable()`:

```
> tstatic = createTable(lstatic, "tstatic")
> tstatic
```

Object of class **aRTtable**

```
Table: "tstatic"
Type: static
Layer: "static"
Rows: 10
Attributes:
  id: character[16] (key)
```

Note that when we create a table it already has 10 rows with the unique ids from the geometries. To add this data to the table we use `updateColumns`, and it also create new columns using `colnames(df)`.

```
> updateColumns(tstatic, df)
> tstatic
```

Object of class **aRTtable**

```
Table: "tstatic"
Type: static
```

```

Layer: "static"
Rows: 10
Attributes:
  id: character[16] (key)
  norm: numeric
  unif: numeric

```

And finally, `getData` is used for reading the data from the table:

```

> getData(tstatic)

  id      norm      unif
1  1 11.984301 97.89574
2 10  7.358129 91.07037
3  2 19.713813 31.62978
4  3 15.566071 89.62430
5  4 21.704297 56.84160
6  5  6.500174 38.60381
7  6  6.332662 36.27251
8  7 11.063396 63.53696
9  8 32.873980 23.49168
10 9 34.684389 11.19028

> df2 = data.frame(id, norm = unlist(lapply(id, function(x) rnorm(1,
+    20, 10)))), unif = unif)
> updateColumns(tstatic, df2)
> getData(tstatic)

  id      norm      unif      uniff
1  1 10.982032 97.89574 97.89574
2 10 49.948164 91.07037 91.07037
3  2  5.710605 31.62978 31.62978
4  3 15.653211 89.62430 89.62430
5  4 36.561501 56.84160 56.84160
6  5 19.498305 38.60381 38.60381
7  6 18.246118 36.27251 36.27251
8  7  4.481289 63.53696 63.53696
9  8 10.616478 23.49168 23.49168
10 9 30.935900 11.19028 11.19028

```

Note that, as `aRT` automatically have created the rows, the order of the rows in the result is not the same of the `df`.

To avoid it, we can create an empty table, and populate it manually. First, we need to use `gen=FALSE`, to avoid generate the rows of the table:

```

> tstatic2 = createTable(lstatic, "tstatic2", gen = FALSE)
> tstatic2

```

Object of class aRTtable

```
Table: "tstatic2"
Type: static
Layer: "static"
Rows: 0
Attributes:
  id: character[16] (key)
```

The argument `gen` indicates that the function must create one row for each spatial object, and fill it with the id of the spatial object. Now we need to create two columns, one of integer type and other of real type, and then we add some rows to the table.

```
> createColumn(tstatic2, "norm", type = "integer")
> createColumn(tstatic2, "unif", type = "numeric")
> addRows(tstatic2, df[1:5, ])
> getData(tstatic2)
```

	id	norm	unif
1	1	12	97.89574
2	2	20	31.62978
3	3	16	89.62430
4	4	22	56.84160
5	5	7	38.60381

```
> addRows(tstatic2, df[6:10, ])
> getData(tstatic2)
```

	id	norm	unif
1	1	12	97.89574
2	2	20	31.62978
3	3	16	89.62430
4	4	22	56.84160
5	5	7	38.60381
6	6	6	36.27251
7	7	11	63.53696
8	8	33	23.49168
9	9	35	11.19028
10	10	7	91.07037

But `addRows` only creates new elements in the table, it cannot change the old elements. For example

```
> addRows(tstatic2, data.frame(id = "1", norm = 2.1, unif = 0.3))
> getData(tstatic2)[1:3, ]
```

	id	norm	unif
1	1	12	97.89574
2	2	20	31.62978
3	3	16	89.62430

We can also create columns of string type, and set the maximum size of the string, as:

```
> createColumn(tstatic2, "charcol", type = "character", length = 5)
> tstatic2
```

Object of class aRTtable

```
Table: "tstatic2"
Type: static
Layer: "static"
Rows: 10
Attributes:
  id: character[16] (key)
  norm: integer
  unif: numeric
  charcol: character[5]
```

`updateColumns()` already calculates the type and the size of the data, before creating the columns.

2.1 External tables

External tables are tables with no geometry associated. Therefore they are created directly from the database, and we can not use **genid**. We create external tables also using `createTable`, as in the next example:

```
> textexternal = createTable(db, "textexternal", id = "myid", length = 5)
> textexternal
```

Object of class aRTtable

```
Table: "textexternal"
Type: external
Rows: 0
Attributes:
  myid: character[5] (key)
```

Note that here we define the name of the key and also its length. It can be defined when creating tables from layers too. As **textexternal** is an object of class **aRTtable** we can use the same functions as described for tables from layers.

2.2 Media tables

Media tables are useful when building databases that will be used in TerraView, or another TerraLib-based GIS. It associates a web page to a double-click in a drawn geometry. This type of table can be created using `type="media"`:

```
> mediatable = createTable(lstatic, type = "media")
```

A layer can have one, and only one, media table, and a media table does not have a name. Also, each media table has two, and only two, attributes: `object_id`, the link to geometries, and `media_name`, a web address.

```
> mediatable
```

Object of class `aRTtable`

```
Type: media
Layer: static
Rows: 0
Attributes:
  object_id: character[50] (key)
  media_name: character[255] (key)
```

A media table can be manipulated as all the other tables, but new columns can not be created. In the next code we associate web pages to each geometry of the layer, and we use `addRows()` to fill the table.

```
> id = getID(xy.spdf)
> url = "http://www.est.ufpr.br/~pedro/media/media"
> name = lapply(id, function(x) sprintf("%s%s.html", url, x))
> name = unlist(name)
> df = data.frame(object_id = id, media_name = name)
> addRows(mediatable, df)
```

To check if it is correct, we can use `getData()`:

```
> getData(mediatable)[1:5, ]

  object_id                               media_name
1         1 http://www.est.ufpr.br/~pedro/media/media1.html
2         2 http://www.est.ufpr.br/~pedro/media/media2.html
3         3 http://www.est.ufpr.br/~pedro/media/media3.html
4         4 http://www.est.ufpr.br/~pedro/media/media4.html
5         5 http://www.est.ufpr.br/~pedro/media/media5.html

> lstatic
```

Object of class `aRTlayer`

```
Layer: "static"
Database: "tabletest"
Number of points: 10
Projection Name: "NoProjection"
Projection Datum: "Spherical"
Tables:
  "tstatic": static
  "tstatic2": static
  "media_layer_1": media
```

3 Attribute queries

We can get all the data of a table using `getData()`. But some operations are useful, for example selecting values that follows a condition, and it can be an attribute, or spatial, or temporal condition. In the case of spatial queries, here we only use the result to get spatial/attribute queries. If you want to see how spatial queries work, see *Spatial Queries*.

To execute database queries, we need to create `aRTtheme` objects.

3.1 Join tables

3.2 Attribute restrictions

3.3 Spatial queries

4 Temporal Tables

Temporal tables in `aRT` work as static tables, noting that there are three identifiers, instead of only one in static tables. The two others are the initial and the final time.

These attributes are strings, but they follow the `TerraLib` model of dates. To convert temporal dates to `aRT` format we will use `toDate()`. This function gets as arguments integer variables `year = 0`, `month = 1`, `day = 1`, `hour = 0`, `minute = 0` and `second = 0` and returns a string describing the date. It is a bit different from `ISOdate`.

```
> toDate(year = 2006, month = 8, day = 7, hour = 6, sec = 5)
```

```
[1] "2006-08-07 06:00:05"
```

```
> ISOdate(year = 2006, month = 8, day = 7, hour = 6, sec = 5)
```

```
[1] "2006-08-07 06:00:05 GMT"
```


4.1 Event tables

An event table represents a temporal table which each element has a static geometry and attributes, but it occurs in a time interval. When we are using an event table, we do not need static tables because each event is unique, and therefore we can put all attributes in the same table. We will use the same layer to create an event table.

```
> lpoints = lstatic
```

To create an event table, we need to set `type="event"` at `createTable()`. The default value of this argument is `"static"` when creating from layers and `"external"` when creating directly from databases.

```
> tevent = createTable(lpoints, "events", type = "event")
> tevent
```

Object of class `aRTtable`

```
Table: "events"
Type: event
Layer: "static"
Rows: 0
Attributes:
  id: character[16] (key)
  time: date (key)
```

When an event table is created, it already contains three attributes: `id`, `itime` and `ftime`, and they are keys. We recommend not to generate ids (`gen=FALSE`), because it would also generate `itime` and `ftime`, and put zero in all time values (0000-00-00 00:00:00).

To fill the event table we will generate a random attribute `value` with duration of 59 minutes, all in the same day:

```
> id = getID(xy.spdf)
> hours = unlist(lapply(id, function(x) round(runif(1, 0, 10),
+      0))))
> time = unlist(lapply(hours, function(x) toDate(y = 2006, month = 3,
+      day = 30, hour = x)))
> value = unlist(lapply(id, function(x) runif(1, 1, 100)))
> df = data.frame(id, value, time)
> df[1:7, ]
```

	id	value	time
1	1	37.292322	2006-03-30 04:00:00
2	2	13.109769	2006-03-30 05:00:00
3	3	98.482764	2006-03-30 01:00:00
4	4	32.542697	2006-03-30 03:00:00

```

5  5 58.776804 2006-03-30 04:00:00
6  6 80.230024 2006-03-30 02:00:00
7  7  4.076095 2006-03-30 01:00:00

```

As the table already has three attributes, we need only to create the column value, and then we can add the rows:

```

> createColumn(tevent, "value", type = "i")
> addRows(tevent, df)
> tevent

```

Object of class aRTtable

```

Table: "events"
Type: event
Layer: "static"
Rows: 10
Attributes:
  id: character[16] (key)
  time: date (key)
  value: integer

```

```

> getData(tevent)

```

	id	time	value
1	1	2006-03-30 04:00:00	37
2	2	2006-03-30 05:00:00	13
3	3	2006-03-30 01:00:00	98
4	4	2006-03-30 03:00:00	33
5	5	2006-03-30 04:00:00	59
6	6	2006-03-30 02:00:00	80
7	7	2006-03-30 01:00:00	4
8	8	2006-03-30 09:00:00	87
9	9	2006-03-30 06:00:00	54
10	10	2006-03-30 01:00:00	40

4.2 Dynamic attribute tables

Dynamic attribute tables work with geometries where one or more attributes changes with the time. It works such as event tables, with the conceptual difference that the identifier may repeat.

4.3 Dynamic geometry tables

(not implemented yet)

4.4 Fully dynamic tables

(not implemented yet)

5 Temporal queries

We can get all table data with `getData()`, but if it is a temporal table, we get it sliced. To do it, we need first to create an `aRTtheme` object.

```
> theme = createTheme(lpoints, "events", table = "events")
> theme
```

Object of class `aRTtheme`

```
Theme: "events"
Layer: "static"
View: "events"
Tables:
  "events"
  Attributes: "id", "time", "value"
```

Attribute Restriction: ""

Note that the theme has two tables ("static" and "events"), and `getData()` returns the join of them.

5.1 Joining tables

5.2 Temporal slicing

To slice the theme data, we need to create an `aRTquerier`, with `openQuerier()`. This function takes as argument `chronon`, representing the type of slides to be produced. It can be "second", "month", "season", "year", "weekofyear" and others, and the default is "nochronon". To exemplify using `aRTquerier`, we implement an algorithm to calculate the number of occurrences in each hour, and the sums of `value`. Therefore we need an `aRTquerier` sliced by hour.

```
> querier = openQuerier(theme, chronon = "hour")
> querier
```

Object of class `aRTquerier`

```
Theme: "events"
Retrieves: geometry
Frames: 0/9
Elements: 0/0
```

To get data from the querier there are two functions. `nextSlide()` loads the next slide, returning the number of elements of it, and `getData()` returns one of the elements of the slide, read from the database. Both functions do not take any argument.

```
> qtde = summary(querier)$slides
```

References

Chambers, J.M., 1998, Programming with data, a guide to the S language.
Springer, New York.